



## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING









$D \Lambda I$		<b>'D'</b>	ľ	ГΙ	ιт	-	
BAI	IVI I	PL	1//	H		FR.	

REV. 001	VALUE	
CENTER WAVELENGTH (CWL)	546 ± 2nm	
FULL WIDTH HALF MAX (FWHM)	10 ± 2nm	
MINIMUM TRANSMISSION	≥85%	
BLOCKING	200 - 1200nm	
SURFACE QUALITY	80-50	
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING	
COATING TYPE	HARD COATED	
DURABILITY	MIL-C-48497A, SECT. 3.4.1	
ENVIRONMENTAL	MIL-STD-801F, SECT. 507.4	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

			Edmund Optics®				
THIRD ANGLE PROJECTION		TITLE	OD4, Ø50mm, 546nm x 10nm, HC, BP I	FILTER			
ALL DIMS IN	mm	DWG NO	65219	SHEET 1 OF 1			