NOTES:

1. SUBSTRATE MATERIAL: BOROFLOAT®

FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

2. PARABOLIC SURFACE:

 $Z=Y^2/[4 * EFL]$ 

3. COATING (APPLY ACROSS CLEAR APERTURE)

S1: PROTECTED GOLD R(avg) >96% @ 700 - 2000 R(avg) >96% @ 2000 - 10000nm S2: NONE


4. EDGES: MOLDED EDGE ACCEPTABLE


5. POWER, IRREGULARITY, SURFACE QUALITY AND COATING SPECIFICATIONS APPLY ACROSS CLEAR APERTURE



6. FINE GRIND SURFACE

7. RoHS COMPLIANT





SECTION C-C

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	
SHAPE	CONCAVE	PLANO	
EFFECIVE FOCAL LENGTH	609.6	N/A	
FOCAL LENGTH TOLERANCE	±1%	N/A	
SURFACE QUALITY	60-40	FINE GRIND	
SURFACE FLATNESS	λ/8	N/A	
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	

	<b>GU</b>			Eamuna Optic	Eamuna Optics®		
THIRD ANGLE PROJECTION		TITLE	6" Diameter x 24" FL Protected Gold Parabolic Mirror	,k			
)	ALL DIMS IN	mm	DWG NO	32069566	SHEET 1 OF 1		