NOTES:

1. SUBSTRATE: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)

\$1: ALUMINUM WITH MULTILAYER OVERCOAT R(AVG) > 95% FROM 450-650nm @ 0° AOI


S2: NONE


3. FINE GRIND SURFACE

- 4. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 5. ROHS COMPLIANT









SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

| | \$1 | \$2 |
|------------------------|----------------------|----------------------|
| SHAPE | CONVEX | PLANO |
| RADIUS | 200mm | N/A |
| SURFACE QUALITY | 60-40 | N/A |
| FOCAL LENGTH TOLERANCE | ±2% | N/A |
| BEVEL | PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED |

| | | | Edmund Optics® | | | | |
|---|------------------------|----|----------------|---|-----------------|--|--|
| | THIRD ANGLE PROJECTION | | TITLE | Ø25mm, -100mm FL ENHANCED ALIUMINUM, CONVEX MIRROR | | | |
| D | ALL DIMS IN | mm | DWG NO | 87669 | SHEET 1 OF 1 | | |