NOTES:

- SUBSTRATE: LIBA 2000+
- 2. CENTERING TOLERANCE (AT 587.6nm): BEAM DEVIATION (HALF ANGLE): <25 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)
 \$1: NONE
 \$2: NONE

EDGE: AS MOLDED





ASPHERIC SURFACE DESCRIBED BY THE FOLLOWING EQUATION AND COEFFICIENTS SHOWN IN TABLE BELOW

$$Z(Y) = \frac{\left(\frac{1}{RADIUS}\right)^{8}Y^{2}}{1+\sqrt{1-(1+k)^{8}\left(\frac{1}{RADIUS}\right)^{2}Y^{2}}} + D^{8}Y^{2} + E^{8}Y^{4} + F^{8}Y^{6} + G^{8}Y^{8} + H^{8}Y^{10} + J^{8}Y^{12} + L^{8}Y^{14} + M^{8}Y^{16}}$$

6. RoHS: COMPLIANT

COEFFICIENT TABLE 5.					
	\$1				
Semi-diameter	25.0				
Coefficient					
(1/RADIUS)	4.794385E-02				
k	-1.057453E+00				
D	0.000000E+00				
Е	7.226537E-06				
F	2.736523E-09				
G	1.590748E-12				
Н	0.000000E+00				
J	0.000000E+00				
Ĺ	0.000000E+00				
М	0.000000E+00				





PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	EFL:	40.00		Edmund Ontice	NO ®
SHAPE	CONVEX	PLANO	BFL:	25.92		Edmund Optics®	
RADIUS	20.858	∞		1		_	
SURFACE QUALITY	As Molded	As Molded	THIRD ANGLE PROJECTION		TITLE	LENS CONDENSER 50mm X 40mm UNCTD TS	
CLEAR APERTURE	Ø44.78	Ø44.78		ı			CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	36171	SHEET 1 OF 1