


## NOTES:


- 1. SUBSTRATE: CRYSTAL QUARTZ
- 2. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 514.5nm DAMAGE THRESHOLD: 3.5 J/cm² @ 10ns @ 1064nm
- 3. SURFACE S1 TO BE PARALLEL TO SURFACE S2 TO WITHIN <0.5 arcsec
- 4. RETARDANCE:  $\lambda/2 \pm \lambda/200$
- 5. TRANSMITTED WAVEFRONT: λ/10 FOR CENTRAL 80% OF CLEAR APERTURE
- 6. Rohs Compliant





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING





SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

<b>Edmund Optics</b>
----------------------

	<b>S</b> 1	\$2	THIRD ANGLE PROJECTION		TITLE	Ø30mm, 514.5nm, λ/2 QUARTZ WAVEPLATE ZERO ORDER	
CLEAR APERTURE	Ø23.0	Ø23.0					
SURFACE QUALITY	10-5	10-5	ALL DIMS IN	mm	DWG NO	48488	SHEET 1 OF 1