
NOTES:


- 1. SUBSTRATE: FUSED SILICA
- 2. S2 TO BE PARALLEL TO S1 TO WITHIN <3ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)
 \$1: SILVER
 R(AVG) >98% from 450-2000nm
 R(AVG) >98% from 2000-10000nm

S2: NONE



- 5. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACE
- 6. SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 7. ROHS: COMPLIANT





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	S2					
SHAPE	PLANO	PLANO				Edmund Option	C®
SURFACE QUALITY	20-10	COMMERCIAL POLISH			W		,5°
SURFACE FLATNESS	0.10 WAVE	N/A		1		MIRROR FS 1/10 WAVE SILV 6.35 DI	ΙΔ
CLEAR APERTURE	Ø5.40	N/A	THIRD ANGLE PROJECTION		TITLE	WIIKKOK 13 1/10 W/WE SIEV 0.33 DI/W	
COATING APERTURE	Ø5.35	N/A					CUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	39187	SHEET 1 OF 1