NOTES:

1. SUBSTRATE:

HOYA GLASS: ND-0.3

FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING

2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN <0.02 mm





COATING SPECIFICATION:
 \$1 & \$2:R(AVG) ≤0.5% @ 600 - 1050nm


5. OPTICAL DENSITY: 3 +/-0.3 @ 400-700nm

6. TRANSMISSION (%): 0.1% AVERAGE FROM 400-700nm

7. ROHS COMPLIANT







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

CO ® Edmi	und Optics®
------------------	-------------

	S1	S2	1		3.0 OD, 25mm DIA., NIR I COATED, ABSORPTIVE ND FILTER		
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION				TITLE
SURFACE QUALITY	80-50	80-50		I		7.555.11.11.2.12	OUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	13177	SHEET 1 OF 1