



NOTES:

- 1. SUBSTRATE:
SILICON (Si)
- 2. SURFACE S2 TO BE PARALLEL TO S1 WITHIN <3 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE)

S1&S2: BBAR(3000-5000nm)
Ravg <3.0% @ 3 - 5µm

4. FINE GRIND SURFACE



- 5. ROHS COMPLIANT



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
CLEAR APERTURE	Ø 45.72	Ø 45.72
SURFACE QUALITY	60-40	60-40
SURFACE FLATNESS	3λ	3λ
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED

 Edmund Optics®			
THIRD ANGLE PROJECTION 		TITLE	50.8mm Dia. x 1mm Thickness 3-5µm Coated Silicon Window
ALL DIMS IN	mm	DWG NO	20039
			SHEET 1 OF 1