NOTES:


- 1. ALLOWABLE OPTICAL MATERIAL: FUSED SILICA CORNING 7980
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN 5 ARCMIN
- 3. COATING (APPLY ACROSS ENTIRE SURFACE) \$1&\$2: VIS-NIR (400-1000nm)

Rabs ≤0.25% @ 880nm Ravg ≤1.25% @ 400 - 870nm Ravg ≤1.25% @ 890 - 1000nm



SIX SIDEWALLS:

SURFACE ACCURACY: COMMERCIAL POLISH



FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

BINLE NOTO / KE FOR KEI ERENGE GIVET				
	\$1	\$2	Ī	
SHAPE	PLANO	PLANO	T P	
IRREGULARITY AT 632.8nm	N/A	N/A		
SURFACE QUALITY	60-40	60-40		

IHIKD ANGLE / A \ C TITLE '		5mm Aperture x 120mm L, VIS-NIR Coo Low NA, Fused Silica Light Pipe	ated,		
	ALL DIMS IN	mm	DWG NO	23498	SHEET 9 OF 18

