

[See all 11 Products in Family](#)

## 100µm 0.22 NA UV/VIS Fiber, 25m Length



Stock **#57-073** [CONTACT US](#)

- 1 + €106<sup>00</sup>

**ADD TO CART**

Volume Pricing	
Qty 1-4	€106,00 each
Qty 5-24	€94,00 each
Need More?	<a href="#">Request Quote</a>

ⓘ Prices shown are exclusive of VAT/local taxes

### Product Downloads

### General

**Note:**

Fiber ends are not polished.

### Physical & Mechanical Properties

110 ±3      Cladding Diameter (µm):

22/11 (Continuous/Momentary)	<b>Minimum Bend Radius (mm):</b>
25.00	<b>Length (m):</b>
124 ±3	<b>Outer Diameter (µm):</b>
100 ±3	<b>Core Diameter (µm):</b>
<b>Optical Properties</b>	
25.4	<b>Acceptance Angle (°):</b>
UVMS	<b>Coating:</b>
Fused Silica	<b>Substrate:</b> <input type="checkbox"/>
0.22	<b>Numerical Aperture NA:</b>
1.457	<b>Index of Refraction (n<sub>d</sub>) - Core:</b>
1.439	<b>Index of Refraction (n<sub>d</sub>) - Cladding:</b>
190 - 1250	<b>Wavelength Range (nm):</b>
±0.02	<b>Numerical Aperture (NA) Tolerance:</b>
<b>Material Properties</b>	
Polyimide	<b>Buffer Material:</b>
<b>Environmental &amp; Durability Factors</b>	
-190 to +390	<b>Operating Temperature (°C):</b>
<b>Regulatory Compliance</b>	
<a href="#">Compliant</a>	<b>RoHS 2015:</b>
<a href="#">Compliant</a>	<b>Reach 209:</b>
<a href="#">View</a>	<b>Certificate of Conformance:</b>

## Product Details

### UV/VIS Optical Fibers

- High OH Content
- Fused Silica Core
- Stepped Index
- Multimode Fiber

### VIS/NIR Optical Fibers

- Low OH Content
- Ideal for Use with NIR Diode Lasers
- Fused Silica Core
- Stepped Multimode Fiber

Buffered Fiber Optics are ideal for regions of the UV/Visible and Visible/NIR spectrum not covered by our plastic optical fibers. These fibers have a fused silica core and cladding, as well as a polymer buffer for added protection. Fiber diameters of 50µm – 600µm feature a high temperature, high strength polyimide buffer, while the 1mm fibers are buffered with nylon for greater protection. Buffered Fiber Optics are offered in UV/MS or VIS/NIR Fibers in 10 and 25m lengths, from 50 to 600µm.

**Note:** Fiber ends are not polished.

## Technical Information

