

[See all 3 Products in Family](#)

10X EO HR Infinity Corrected Objective



10XEO HR Infinity Corrected Objective (#58-372)

Stock **#58-372** **7 In Stock**

-

1

+

€2.980⁰⁰

ADD TO CART

Volume Pricing	
Qty 1-4	€2.980,00 each
Qty 5+	€2.830,00 each
Need More?	Request Quote

! Prices shown are exclusive of VAT/local taxes

Product Downloads

General	
28-20-45-000	Model Number:
Compatible Tube Lens Focal Length (mm): Focal Length: 200mm	
Microscope Objective	Type:
Infinity Corrected	Style:

Physical & Mechanical Properties	
76.00	Length excluding Threads (mm):
34	Maximum Diameter (mm):
205.00	Weight (g):
Optical Properties	
0.64mm	Horizontal Field of View, 1/2" Sensor:
0.88mm	Horizontal Field of View, 2/3" Sensor:
11.00	Field Stop Diameter (mm):
20.00	Focal Length FL (mm):
10X	Magnification:
0.45	Numerical Aperture NA:
0.74	Resolving Power (µm):
2.70	Depth of Field (µm):
19.00	Working Distance (mm):
400 - 700	Wavelength Range (nm):
95	Parfocal Length (mm):
N/A	Immersion Liquid:
Threading & Mounting	
M26 x 36 TPI	Mounting Threads:

Environmental & Durability Factors	
+23 ±5	Operating Temperature (°C):
30 - 70%	Operating Humidity:


Regulatory Compliance	
Compliant	RoHS 2015:
View	Certificate of Conformance:
Compliant	Reach 235:

Product Details

- High Resolving Power
- Designed for use in Zoom Lens Systems
- Features Mtutoyo Standard M26 x 36 TPI Threads

EO High Resolution Infinity Corrected Objectives are designed for high resolution over a small field of view. These objectives feature Mtutoyo standard M26 x 36 TPI threads and a 95mm parfocal length which allows them to be used interchangeably with Mtutoyo microscopes and accessories. While usable with Mtutoyo microscopes and accessories, these objectives perform best when used in a zoom lens system. EO High Resolution Infinity Corrected Objectives feature near-diffraction limited on axis performance. For longer working distance objectives that can be used in Mtutoyo systems, see our [EO Infinity Corrected Long Working Distance Objectives](#).

Technical Information



;