TECHSPEC®

12.7mm Square Grade PCX Cylinder Lens



Stock **#13-479** **17 In Stock**

- 1 +

€209,00

ADD TO CART

Volume Pricing	
Qty 1-5	**€209,00** each
Qty 6-25	**€187,00** each
Qty 26-49	**€179,00** each
Need More?	**Request Quote**

Prices shown are exclusive of VAT/local taxes

Product Downloads

STEP:step | Curve:pdf | PDF Drawing:pdf | IGES:igs | Curve (xslx):xlsx | Zemax:zar | Zemax:zmx | eDrawing:eprt | Code V:seq | EO Spec Sheet

Download All

General

Type:	Cylinder Lens, Plano-Convex

Physical & Mechanical Properties

Bevel:	Protective as needed	**Center Thickness CT (mm):**	3.00
Center Thickness Tolerance (mm):	±0.1	**Clear Aperture CA (mm):**	11.43 x 11.43
Dimensional Tolerance (mm):	+0.0/-0.025	**Dimensions (mm):**	12.7 x 12.7
Edge Thickness ET (mm):	2.71	**Axial Twist (arcmin):**	<3

Optical Properties

Effective Focal Length EFL (mm):	150.00	**Substrate:** ⓘ	**Fused Silica** (Corning 7980)
f/#:	12	**Numerical Aperture NA:**	0.04
Coating:	Laser V-Coat (355nm)	**Back Focal Length BFL (mm):**	147.94
Coating Specification:	R_{abs} <0.25% @ 355nm	**Design Wavelength DWL (nm):**	355

Focal Length Specification Wavelength (nm):	587.6	**Radius R_1 (mm):**	68.77
Surface Quality:	20-10		
Power (P-V) @ 632.8nm:	1.5λ		
Plano Axis Wedge (arcmin):	<3	**Power Axis Wedge (arcmin):**	<4.5

Regulatory Compliance

RoHS 2015:	**Compliant**	**Reach 209:**	**Compliant**
Certificate of Conformance:	**View**		

Need different specs or modifications?

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our **custom manufacturing capabilities** or submit an inquiry **here.**

Product Details

- <0.25% AR Coated for Nd:YAG Harmonics
- <3 Arcminute Wedge Tolerance
- Fused Silica Substrate

TECHSPEC® Laser Grade Laser Line Cylinder Lenses are manufactured with tightly controlled geometric wedge tolerances to facilitate drop in compatibility. These laser line cylinder lenses feature laser grade optical specifications including 20-10 surface quality and λ/4 surface irregularity on both plano and cylindrical surfaces. TECHSPEC Laser Grade Laser Line Cylinder Lenses are available in 266nm, 355nm, 532nm, and 1064nm AR coated versions, with specified laser induced damage thresholds. These fused silica lenses are ideal for demanding laser machining and medical applications.

Related Products



Metric Rectangular Optic Mounts



Laser Grade Broadband Cylinder Lenses

Laser Beam Shaping



Cylinder Lenses

Frequently Purchased Together

#88-425 – Coherent® PowerMax Wand 1299161 | 325 – 1065nm
€2.075,00

Qty

Na
€425,00

Qty



PCX Cylinder Lens
€209,00

Qty

#37-720 – 12.7mm Dia., 532nm T, 355nm R 45° Harmonic Separator
€226,00

Qty

Resources

Media Type

- Application Note
- Trending in Optics
- Published Article
- FAQ
- Glossary
- Video

APPLICATION NOTE
Anti-Reflection (AR) Coatings

APPLICATION NOTE
Laser Beam Shaping Overview

TRENDING IN OPTICS
Non-Circular Optics for System Miniaturization

APPLICATION NOTE
What are Cylinder Lenses?

APPLICATION NOTE
Considerations When Using Cylinder Lenses

PUBLISHED ARTICLE
Cylinder Lenses for Beam Shaping

View More

;