

TECHSPEC[®] 25.4mm Dia., 550 - 1050nm, 50R:50T, Ultrafast Beamsplitter



TECHSPEC[®] Ultrafast Beamsplitters

Stock **#17-068** 4 In Stock

-

1

+

€645⁰⁰

ADD TO CART

Volume Pricing	
Qty 1-9	€645,00 each
Qty 10+	€575,00 each
Need More?	Request Quote

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

General

BS1631

Model Number:

Ultrafast Non-Polarizing Beamsplitter

Type:

Physical & Mechanical Properties

1.00

Thickness (mm):

25.40 +0.00/-0.05	Diameter (mm):
80	Clear Aperture (%):
<10	Parallelism (arcsec):
Optical Properties	
Fused Silica (Corning 7980)	Substrate: □
10-5 (substrate)	Surface Quality:
45	Angle of Incidence (°):
550 - 1050	Wavelength Range (nm):
50/50	Reflection/Transmission Ratio (R/T):
Coating Specification: Surface 1: R _{avg} = 50% @ 550 - 1050nm R _p = 35±3% @ 550 - 1050nm R _s = 67±3% @ 550 - 1050nm Surface 2: R _s <2% @ 550 - 1050nm R _p <1.5% @ 550 - 1050nm	
GDD Specification: Transmission: 0 fs ² @ 550 - 1050nm Reflectivity: 0 fs ² @ 550 - 1050nm	
<λ/10 @ 632.8nm	Transmitted Wavefront Distortion:
<λ/10 @ 632.8nm	Reflected Wavefront Distortion:

Regulatory Compliance	
Compliant	RoHS 2015:
View	Certificate of Conformance:
Compliant	Reach 235:

Product Details

- Designs for Ti:sapphire and Yb:doped Fiber Lasers
- 90:10, 70:30, and 50:50 (R:T) Split Ratios
- Controlled Reflection and Transmission GDD

TECHSPEC® Ultrafast Beamsplitters are designed for use with femtosecond pulsed Ti:sapphire and Yb:doped fiber lasers. Their front surface features a 90:10, 70:30, or 50:50 (R:T) non-polarizing beamsplitter coating while their back surface features an anti-reflective coating to minimize losses due to reflection. Each coating has controlled dispersion to allow for predictable group delay dispersion (GDD) of the transmitted or reflected pulses. TECHSPEC Ultrafast Beamsplitters are available in standard imperial sizes for easy integration into optical systems. Please [contact us](#) if your application requires an Ultrafast Beamsplitter with a custom size or coating specifications.

Note: The arrow on the edge of these optics points towards the beamsplitter coating.

Technical Information



