

**TECHSPEC® 25mm Dia., 0.25 NA, Uncoated 1550nm NIR Aspheric Lens**



Stock **#17-421** **6 In Stock**

[Other Coating Options](#)

1  €374<sup>.92</sup>

**ADD TO CART**

Volume Pricing	
Qty 1-5	€374,92 each
Qty 6-25	€299,73 each
Qty 26-49	€282,22 each
Need More?	<a href="#">Request Quote</a>

**i** Prices shown are exclusive of VAT/local taxes

Product Downloads

**SPECIFICATIONS**

**General**

Aspheric Lens **Type:**

## Physical & Mechanical Properties

25.00 +0.0/-0.025 **Diameter (mm):**

<2.5 **Centering (arcmin):**

22.5 **Clear Aperture CA (mm):**

6.43 **Edge Thickness ET (mm):**

8.50 ±0.1 **Center Thickness CT (mm):**

Protective as needed **Bevel:**

Plano **Shape of Back Surface:**

## Optical Properties

50.00 @ 1550nm **Effective Focal Length EFL (mm):**

0.25 **Numerical Aperture NA:**

42.65 @ 587.6nm **Back Focal Length BFL (mm):**

N-SF6 **Substrate:**

1550 **Aspheric Design Wavelength (nm):**

Uncoated **Coating:**

40-20 **Surface Quality:**

2 **f#:**

Infinite **Conjugate Distance:**

0.4λ RMS and 2λ PV **Asphere Figure Error, @ 632.8nm:**

20.00 **Power (diopters):**

## Regulatory Compliance

[View](#) **Certificate of Conformance:**

## PRODUCT DETAILS

- Designed at 1550nm
- Precision Grade Aspheric Surface
- Uncoated and <0.25% Reflectance V-Coat Options

TECHSPEC® 1550nm Precision Near-Infrared (NIR) Aspheric Lenses are designed at 1550nm to eliminate spherical aberration in the near-infrared. 1550nm lasers are commonly used in telecom, LiDAR, and other applications requiring eye-safe design features. Manufactured from S-TiH6 or N-SF6 substrates and polished through a computer numerical controlled (CNC) process, these aspheric lenses achieve high precision performance across the NIR spectrum. Featuring a 0.4λ RMS aspheric figure error, these lenses are ideal for applications that require spherical aberration correction, including imaging and laser focusing applications. TECHSPEC® 1550nm Precision Near-Infrared (NIR) Aspheric Lenses are available with low numerical aperture designs for applications that require beam shape to be maintained as well as high numerical aperture designs for light-gathering applications. For custom designed CNC polished aspheric lenses, please contact us.

## CUSTOM

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).

## COMPATIBLE MOUNTS