

TECHSPEC® 3X, 40mm WD, In-Line CompactTL™ Telecentric Lens



40mm WD, 3X, In-Line Version (Left) and MS Version (Right)



Stock #67-321 **20+ In Stock**

⊖ 1 ⊕ €1.045⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	€1.045,00 each
Need More?	Request Quote

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

General

CompactTL™ Series **Product Family:**
Edmund Optics® **Manufacturer:**
Telecentric Lens **Type:**

Compatible Light Guide/Source:
1/4" (0.312") and 1/8" (0.187")

Type of Illumination:
In-Line Illumination

Physical & Mechanical Properties

Fixed Iris Option:

52.25 Length (mm):

52.25 Length excluding Threads (mm):

18.00 Maximum Diameter (mm):

45 Weight (g):

Optical Properties

2.9mm Horizontal Field of View, 2/3" Sensor:

2.1mm Horizontal Field of View, 1/2" Sensor:

1.6mm Horizontal Field of View, 1/3" Sensor:

11.00 Maximum Image Circle (mm):

0.093 Numerical Aperture NA, Object Side:

±1 Working Distance Tolerance (mm):

6 (4) Number of Elements (Groups):

0.055 Typical Telecentricity @ 588nm (°):

0.1576 Typical Distortion @ 588nm (%):

3X Primary Magnification PMAG:

3.00 Telecentric Lens Magnification:

40 Working Distance (mm):

2.9 x 2.2 FOV @ Max Sensor Format, H x V (mm):

f/16 Aperture (f/#):

M4 MgF₂ Coating:

±0.08mm (20% @ 20 lp/mm) Depth of Field (mm):

3X Magnification:

VIS Lens Wavelength Range:

Sensor

2/3" Maximum Sensor Format:

4.50 Pixel Size (µm):

Threading & Mounting

M25.5 x 0.50 (Female) Filter Thread:

#88-212 (Required) Filter Thread Adapter:

M16 x 0.5 (Female) Front Thread:

C-Mount Mount:

Regulatory Compliance


Compliant RoHS 2015:

Product Details


- 2/3", C-Mount Telecentric Lens
- Up to 2.3 MegaPixels, 4.5µm Pixel Size Sensors
- Small Telecentric Lens with Coaxial Illumination Options

TECHSPEC® CompactTL™ Telecentric Lenses are designed for applications with tight space constraints due to their ultra-compact design. These lenses feature a 2/3" sensor format and a variety of different working distance and magnification options. From single unit to high volume implementation, these lenses provide a great price to performance ratio. TECHSPEC® CompactTL™ Telecentric Lenses are perfect for integration into gauging systems due to their excellent telecentricity and low distortion. The fixed iris and lockable focus make these lenses ideal for implementation into factory floors and assembly lines, as they will remain fixed over time.


Technical Information




#67-321, 3X, 40mm WD, In-Line CompactTL™ Telecentric Lens, Distortion Plot




#67-321, 3X, 40mm WD, In-Line CompactTL™ Telecentric Lens, Relative Illumination Plot



#67-321, 3X, 40mm WD, In-Line CompactTL™ Telecentric Lens, Telecentricity Plot



#67-321, 3X, 40mm WD, In-Line CompactTL™ Telecentric Lens, Modulated Transfer Function (MTF) Plot, 40mm Working Distance, f16



#67-321, 3X, 40mm WD, In-Line CompactTL™ Telecentric Lens, Depth of Field Plot, 40mm Working Distance, f16