

[All Products](#) / [Optics](#) / [Optical Lenses](#)

[See all 37 Products in Family](#)

5.5" x 5.5", 10" F



Aspherically Contoured Fresnel Lenses

Please select your shipping country to view the most accurate inventory information, and to determine the correct Edmund Optics sales office for your order.

Select Your Country/Region: European Union

Submit

1

€122^{,00}

ADD TO CART

Volume Pricing

Qty 1-10 €122,00 each

Qty 11-49 €110,00 each

Need More? [Request Quote](#)

Prices shown are exclusive of VAT/local taxes

Product Downloads

- Zemax:zar
- Zemax:zmx
- Code V:seq
- EO Spec Sheet
- [Download All](#)

General

Type: Fresnel Lens

Physical & Mechanical Properties

Center Thickness CT (inches): 0.06

Dimensional Tolerance (inches): ±0.05

Dimensions (inches): 5.5 x 5.5

Dimensions (mm): 139.7 x 139.7

Effective Diameter (inches): 5.0

Thickness Tolerance (%): ±40

Optical Properties

Effective Focal Length EFL (mm): 254.00

Substrate: Acrylic

Coating: Uncoated

Wavelength Range (nm): 400 - 1100

Effective Focal Length EFL (inches): 10.00

Groove Density (grooves/inch): 100.00

Index of Refraction (n_d): 1.49

Transmission (%): 85 (Typical)

Environmental & Durability Factors

Operating Temperature (°C): 80 (Maximum)

Regulatory Compliance

RoHS 2015: **Compliant**

Certificate of Conformance: [View](#)

Product Details

- Positive Focal Length
- Square and Rectangular Options
- Ideal for Light Gathering Applications

Fresnel Lenses replace the curved surface of a conventional lens with a series of concentric grooves, molded into the surface of a thin, lightweight plastic sheet. The grooves act as individual refracting surfaces, like tiny prisms when viewed in cross section, bending parallel rays in a very close approximation to a common focal length. Because the lens is thin, very little light is lost by absorption. Fresnel Lenses are a compromise between efficiency and image quality. High groove density allows higher quality images, while low groove density yields better efficiency (as needed in light gathering applications). In infinite conjugate systems, the grooved side of the lens should face the longer conjugate.

Fresnel lenses are most often used in light gathering applications, such as condenser systems or emitter/detector setups. Fresnel lenses can also be used as magnifiers or projection lenses; however, due to the high level of distortion, this is not recommended.

Please select your shipping country to view the most accurate inventory information, and to determine the correct Edmund Optics sales office for your order.

Select Your Country/Region:

Technical Information

Related Products



Fixed Filter Mounts

Frequently Purchased Together



#03-666 - 8.0 - 118.0 Optic Height,
English Bar-Type Optic Holder
€120,00

Qty



#27-501 - 100mm Dia x 200mm
Focal Length, PCX Condenser Lens
€126,00

Qty



#32-591 - 3.0" x 3.0", 3" Focal
Length, Fresnel Lens
€50,50

Qty



#32-592 - 3.0" x 3.0", 3.9" Focal
Length, Fresnel Lens
€50,50

Qty



Resources

Media Type

- Video
- Glossary

▶ VIDEO

Fresnel Lens
Review

GLOSSARY

Fresnel lens

▶ VIDEO

How to
Determine
Magnification
of an Optical...

Please select your shipping country to view the most accurate inventory information, and to determine the correct Edmund Optics sales office for your order.

Select Your Country/Region:

Lens Setup

? FAQ

How do I clean my optics?