Edmund

In order to provide more accurate inventory information, please select your shipping country:

Select Your Country/Region: European Union

SUBMIT

850nm CWL, 10nm FWHM, 25mm Mounted Diameter

Stock **#67-852** 3-4 DAYS

Additional Bandwidths

- 1 + **€165,00**

ADD TO CART

Qty 1-9
€165,00

Qty 10+
€148,30

Volume Pricing
Request Quote

Prices shown are exclusive of VAT/local taxes

Get Product Downloads

Diameter (mm):
25.00 +0.00/-0.25

Angle of Incidence (°):
0

Optical Density OD (Average):

≥4.0

Clear Aperture CA (mm):
21.0

Center Wavelength CWL (nm):
850.00 +3.0/-1.0

Center Wavelength CWL Tolerance (nm):
+3.0/-1.0

Full Width-Half Max FWHM (nm):
10.00 ±2

Full Width-Half Max FWHM Tolerance (nm):
±2

Minimum Transmission (%):
>50

Operating Temperature (°C):
-50 to +70

Coating:
Traditional Coated

Surface Quality:
80-50

Thickness Tolerance (mm):
±0.1

Type:
Bandpass Filter

Typical Applications:
General Filtering

Blocking Wavelength Range (nm):
200 - Far IR

Construction:
Mounted in Black Anodized Ring

Mount Thickness (mm):
5.9 ±0.1

Regulatory Compliance

RoHS 2015:
Compliant

Certificate of Conformance:
View

Reach 235:
Compliant