

[See all 15 Products in Family](#)

Coherent® EnergyMax 1110572 | 500µJ-1000mJ, DB25

See More by [Coherent®](#)



Coherent® EnergyMax Laser Energy Sensors

Stock #12-391 **3 In Stock**

- 1 + €2.215⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	€2.215,00 each
Need More?	Request Quote

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

General

J-50MJV-248 w/ Diffuser
Coherent Part Number: 1110572

Model Number:

[Meter required](#)

Type:

±3

Linearity (%):

±3

Calibration Uncertainty (%):

<16	Noise Equivalent Energy (μJ):
#35-203	Compatible Meters:
520mJ/cm ² (10ns, 248nm)	Maximum Incident Energy Density:
500 μJ - 1J	Energy Range:
#88-412	Preferred Meter:
Physical & Mechanical Properties	
50	Active Area Diameter (mm):
Optical Properties	
248	Calibration Wavelength (nm):
86	Maximum Pulse Width (μs):
190 - 266	Wavelength Range (nm):
Sensor	
Pyroelectric	Type of Sensor:
Electrical	
200	Maximum Repetition Rate (pps):
15	Maximum Incident Beam Power (W):
Hardware & Interface Connectivity	
DB25	Connector:
2.5	Length of Cable (m):
Regulatory Compliance	
Exempt	RoHS 2015:
Contains SVHC(s)	Reach 224:
View	Certificate of Conformance:

Product Details

- ISO 17025 Certified
- Embedded Spectral Compensation Characteristics
- Automatic Temperature Compensation

Coherent® EnergyMax Laser Energy Sensors are designed for a variety of demanding laser measurement applications. These energy sensors, available in meter or meterless USB configurations, incorporate a diffuse coating to minimize specular reflection and feature large active areas. The J-50MB-YAG combines the MaxBlack coating with a diffuser for use with high energy lasers of up to 3J. Coherent® EnergyMax Laser Energy Sensors utilize onboard sensors to automate temperature compensation for improved measurement accuracy.