

Coherent® FieldMate Laser Power Meter 1098297

See More by [Coherent®](#)



#59-978 (sensor sold separately)

Stock **#59-978 2 In Stock**

-

1

+

€1.150⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	€1.150,00 each
Need More?	Request Quote

i Prices shown are exclusive of VAT/local taxes

Product Downloads

General	
1098297	Model Number:
Power Only	Type:
±1	Display Accuracy (%):
±1.0	Calibration Uncertainty (%):

Note:
Coherent® [Thermopile Power Sensors](#), [Position Sensing Thermopile Power Sensors](#), [Laser Energy Sensors](#), or [High Sensitivity Sensors](#) Sold Separately

Physical & Mechanical Properties

193.00	Length (mm):
117.00	Width (mm):
0.8	Weight (kg):
46	Depth (mm):

Optical Properties

0.1% of Full Scale (10s Scale)	Resolution:
--------------------------------	-------------

Electrical

0 to 2 V	Analog Output:
20	Power Sampling Rate (Hz):

Hardware & Interface Connectivity

100-240 V AC, 50/60 Hz OR 2 9V alkaline batteries	Power Supply:
---	---------------

Environmental & Durability Factors

+5 to +40	Operating Temperature (°C):
-20 to +70	Storage Temperature (°C):

Regulatory Compliance

Exempt	RoHS 2015:
Contains SVHC(s)	Reach 224:
View	Certificate of Conformance:

Product Details

- Coherent® [Thermopile Power Sensors](#), [Position Sensing Thermopile Sensors](#), [Laser Energy Sensors](#), or [High Sensitivity Sensors](#) Sold Separately
- FieldMate Used to Measure Laser Power
- FieldMaxII Used to Measure Laser Power and Energy
- ISO 17025 Certified

Coherent® Laser Power and Energy Meters are designed to accurately measure and help tune the power or energy of continuous wave and pulsed lasers. The FieldMate, which features an analog needle with a large LCD display, is compatible with thermopile or optical sensors and is an economical solution for measuring laser power when advanced data analysis is not necessary. The FieldMaxII utilizes a large, backlit LCD screen and features a USB interface for computer connectivity. Coherent® Laser Power and Energy Meters feature FieldMaxII-TO, which is compatible with thermopile or optical sensors, while the FieldMaxII-TOP is compatible with thermopile, optical, or pyroelectric sensors. The LabMax is an all-in-one solution for measuring laser power or energy and is ideal for applications requiring advanced data analysis. The LabMax-TOP is compatible with thermopile, optical, or pyroelectric sensors. The LabMax Pro is the most advanced power and energy meter and is compatible with thermopile, optical, and pyroelectric sensors, as well as the PowerMaxPro high speed sensor technology. The LabMax Pro can provide advanced analysis up to 625kHz.