JAI Go, 8105M-5GE-UV , 2/3" 8.1MP, 5GigE UV Camera

Stock **#29-162** **1 In Stock**

- 1 + **€7.980**.00

ADD TO CART

Volume Pricing	
Qty 1+	**€7.980,00** each
Need More?	Request Quote

Prices shown are exclusive of VAT/local taxes

Product Downloads

SPECIFICATIONS

General

Type:	UV Camera
Model Number:	GO-8105M-5GE-UV
Manufacturer:	

JAI

Camera Series:
Go

Spectrum:
UV

Physical & Mechanical Properties

Dimensions (mm):
29 x 29 x 68

Weight (g):
94

Housing:
Full

Sensor

Sensor Format:
2/3"

Resolution (Megapixels):
8.10

Frame Rate (fps):
66.00

Pixels (H x V):
2,856 x 2,848

Pixel Size, H x V (µm):
2.74 x 2.74

Sensing Area, H x V (mm):
7.8 x 7.8

Imaging Sensor:
Sony IMX487-AAMJ

Type of Sensor:
Progressive Scan CMOS

Shutter Type:
Global

Pixel Depth:
8/10/12 Bit

Machine Vision Standard:
GigE Vision

Electrical

Power Consumption (W):
5.4

Hardware & Interface Connectivity

Interface:
GigE (PoE)

Connector:
RJ45 with Screw Locks

Power Supply:
Power Supply Required and Sold Separately:
USA: #29-171
Europe: #29-171
Japan: #29-171
Korea: Not Available
China: Not Available

Synchronization:
Hardware Trigger (GPIO) or Software Trigger

Interface Port Orientation:
Back Panel

GPIO Connector Type:
6-pin Hirose

Threading & Mounting

Mount:
C-Mount

Environmental & Durability Factors

Operating Temperature (°C):
-5 to +45

Storage Temperature (°C):
-25 to +60

Regulatory Compliance

Certificate of Conformance:
View

PRODUCT DETAILS

- >40% Quantum Efficiency at 280 – 400nm UV Wavelengths
- Up to 8.1MP Resolution
- Sony Pregius Sensor, With Xscale Functionality

JAI® Go Series UV Cameras are designed for high resolution output in UV wavelengths ranging from 280 – 400nm. Utilizing the Sony Pregius S sensor's Xscale function, sub-pixel rescaling of outputs is possible allowing for easier integration into existing systems. With a small form factor, 100g weight, and shock and vibration ratings of 80G/10G, these cameras are highly reliable in rugged environments. JAI® Go Series UV Cameras feature >25% quantum efficiency at 200nm which increases to >40% in its 280 – 400nm designed wavelength range. These cameras are ideal for applications including machine vision, inspection, video microscopy, and UV spectroscopy.

Note: Downloadable software is **available** online.

Designed for excellent performance in the UV spectrum, JAI GO UV Cameras leverage the Sony IMX487-AAMJ sensor and 5GigE interface to deliver high-resolution performance for demanding applications. With global shutter technology and progressive scan output, these cameras capture sharp UV images even in fast-moving environments. Compact and rugged, with a C-Mount housing and broad operating temperature range, they offer exceptional flexibility for machine vision, UV fluorescence inspection, and spectroscopy setups requiring stable and reliable imaging across the 280–400nm range.

FAQ(s)

What sensor is used in JAI GO UV Cameras?
These cameras utilize the Sony IMX487-AAMJ progressive scan CMOS sensor, optimized for UV imaging performance.

How are these UV cameras suited for rugged environments?
With a compact form factor, C-Mount design, 94g weight, and shock/vibration ratings of 80G/10G, they are highly reliable even under challenging conditions.

What applications are best suited for JAI GO UV Cameras?
They are ideal for fluorescence imaging, machine vision, surface inspection, video microscopy, and spectroscopy, which require precise, stable imaging.

How does global shutter technology benefit UV imaging?
Global shutter ensures accurate capture of fast-moving objects without distortion, which is critical for dynamic inspection and high-speed UV imaging tasks.