

[See all 3 Products in Family](#)

Reflectance Integrating Sphere

See More by [Ocean Optics](#)



Stock **#90-587** NEW [CONTACT US](#)

- 1 + €3.584.⁰⁰

ADD TO CART

Volume Pricing

Qty 1+	€3.584,00 each
Need More?	Request Quote

! Prices shown are exclusive of VAT/local taxes

Product Downloads

10.32 **Diameter of Entrance Port (mm):**

SMA905 **Fiber Connector Type:**

General

ISP-REFL **Model Number:**

Note:
Provides even surface illumination for reflectance measurements of surfaces such as the color of flat samples

Lamp Lifetime (hours):
900 hours

Title:
Reflectance Integrating Sphere

Physical & Mechanical Properties

Weight (g):
864.7

Dimensions (mm):
54 x 57 x 83

Diameter (mm):
38.10

Optical Properties

Coating:
Spectralon® doped with BaSO₄

Spectral Range:
~360–2500 nm

Environmental & Durability Factors

Color Temperature (K):
3100

Regulatory Compliance

RoHS 2015:
[Compliant](#)

Certificate of Conformance:
[View](#)

Reach 250:
[Compliant](#)

Product Details

- Measure Total Irradiance or Reflectance with Models Optimized for Emission Sources or Surface Illumination
- Ideal for UV–NIR Applications in Materials Testing, LEDs, Lasers, and More
- White Reflectance Standard Provides Stable, Repeatable Reference Measurements
- Compatible with Ocean Optics Spectrometers and Accessories

Ocean Optics integrating spheres provide flexible, accurate solutions for measuring light output or surface reflectance across a wide spectral range. Whether you need 360° field-of-view irradiance collection, uniform surface illumination for reflectance measurements, or a stable reference for calibration, these integrating spheres ensure consistent, reliable results. The White reflectance standard ([#90-586](#)) complements the spheres by providing a dependable calibration reference for diffuse reflectance measurements. Ocean Optics Integrating Spheres are well-suited for UV-NIR applications, including material testing, LED analysis, and laser measurements.

Selection Guide:

FOIS-1 ([#90-588](#)): Best for **irradiance measurements** and light emission sources; features a 360° field of view for collecting light from LEDs, lasers, and other broad light fields.

ISP-REF ([#90-587](#)): Best for **surface reflectance measurements**; provides even surface illumination and integrates a transfer optic and built-in light source for easy measurement of color or reflectivity on opaque or directional samples.

WS-1 ([#90-586](#)): Use alongside your integrating sphere for reliable white reference measurements when calibrating for diffuse reflectance.